

32" LCD PC

Wide format & sharp display



32" TFT LCD monitor

- . Display Colors: 16.7M
- . Number of Pixels: 1366 x 768
- . Aspect Ratio: 16 : 9
- . Brightness: 500 cd/m²
- . Contrast Ratio: 1500 : 1

Wide format & sharp display Ideal for public display and advertising

32" LCD PC for Digital Signage

System Information



- . For MV700A M/B : VIA Eden ULV 1GHz CPU, CX700M chipset
- . 1 x DDRII up to 1GB
- . IDE / CF Socket / SATA
- . Support SPDIF, Audio Amplifier (Option)
- . 1 x Line-in & Line-out
- . 1 x Audio Out RCA Jack L & R
- . 1 x LAN Realtek 8100C 10/100M
- . 1 x PS/2 Keyboard & Mouse
- . 2 x USB 2.0
- . 1 x Video-In
- . 1 x COM RS232 port
- . 2 x PCI & mini PCI
- . Mounting Spec. : VESA 200, 200 x 200 mm
- . Power Input : Rated Input 100V / 240V, Voltage range 90 ~ 264 Vac, Current 100 Vac, 240 Vac/full load (3.4A), Frequency 47~63Hz
- . Power Output : Total 276W. DC24V / 8.0A ; DC12V / 5.3A ; DC5VSB / 5A
- . Dimension : 120 H x 959 W x 542 D mm
- . Weight : 22 Kg
- . Operating Temp : 0~40°C Fanless
- . Operating Humidity : 10~80% RH 50°C

