

32" LCD PC

Wide format & sharp display



Wide format & sharp display
Ideal for public display and advertising

32" LCD PC for Digital Signage

System Information



- . VIA C7 1GHz CPU, CX700M chipset
- . 1 x DDR up to 1GB
- . IDE / CF Socket / SATA
- . Support S-Video, SPDIF, Audio Amplifier (Option)
- . 1 x Line-in & Line-out
- . 1 x Audio Out RCA Jack L & R
- . 1 x LAN Realtek 8100C 10/100M
- . 1 x PS/2 Keyboard & Mouse
- . 2 x USB 2.0
- . 1 x Video-In
- . 1 x COM RS232 port
- . 2 x PCI & mini PCI
- . Mounting Spec.: VESA 200, 200 x 200mm
- . Power Input: Rated Input 100V/240V, Voltage range 90~264Vac, Current 100Vac, 240Vac/full load(3.4A), Frequency 47~63Hz
- . Power Output: Total 276W. DC24V / 8.0A; DC12V / 5.3A; DC5VSB / 5A
- . Dimension: 120(H) x 959(W) x 542(D) mm
- . Weight: 22Kg
- . Operating Temp: 0~40°C Fanless
- . Operating Humidity: 10~80% RH 50°C

32inches TFT LCD monitor

- . Display Colors: 16.7M
- . Number of Pixels: 1366 x 768
- . Aspect Ratio: 16 : 9
- . Brightness: 500 cd/m²
- . Contrast Ratio: 1500 : 1

