

42" LCD PC

SIZE DOES MATTER!

The Active Matrix LCD screen creates the most powerful visual images!



42" LCD PC for Digital Signage

System Information



- . Intel Pentium M/Celeron M CPU, 82852GM+ICH4 chipset
- . 1 x DDR up to 1GB
- . IDE / CF Socket
- . TV-OUT ,WDT/DIO, Audio Amplifier (Option), SPDIF
- . 1 x LAN Realtek 8100C 10/100M
- . 1 x PS/2 Keyboard & Mouse
- . 2 x USB 2.0
- . 2 x IEEE1394
- . 1 x Video-In
- . 1 x PCI & mini PCI
- . 1 x Audio Out RCA Jack L & R
- . Mounting Spec.: 600 x 200mm
- . Power Input: Rated Input 100V/240V, Voltage range 90~264Vac, Current 100Vac, 240Vac/full load(3.4A), Frequency 47~63Hz
- . Power Output: Total 276W. DC24V / 8.0A; DC12V / 5.3A; DC5VSB / 5A
- . Dimension: 120(H) x 1031(W) x 623(D) mm
- . Weight: 28Kg
- . Operating Temp: 0~40°C Fanless
- . Operating Humidity: 10~80% RH 50°C

42inches TFT LCD monitor

- . Display Colors: 16.7M
- . Number of Pixels: 1920 x 1080
- . Aspect Ratio: 16 : 9
- . Brightness: 500 cd/m²
- . Contrast Ratio: 1500 : 1

